

# DOOR STATION

*The Door Station provides an exceptional Video and Audio Intercom experience in combination with Video Intercom touch screens to provide customers the ability to monitor and communicate with their front doors, gates or entryways.*

## **FEATURES:**

- *Delivers full-motion video and high-quality audio intercom for crystal-clear communications and video security throughout a home or business.*
- *See who's at the front door from any room, or even from the backyard, when used with Control4 Touch Screens with integrated camera.*
- *Features motion detection, fast connection speed and camera snapshots to mobile devices.*
- *Available in flush-mount and surface-mount options, and with or without integrated keypad.*

# Control4® DS2 Door Station



## Control4 DS2 Door Station (C4-DS2FM, C4-DS2FMKP, C4-DS2SM, C4-DS2SMKP)

The Control4 DS2 Door Station delivers an amazing audio and HD video intercom experience, enabling customers to monitor and communicate with the front door or their security gate. Combined with Control4 touch screens, customers enjoy greater convenience and peace of mind throughout the home.

- Available in flush-mount and surface-mount options
- Optional integrated keypad is ideal for customers with gates or for those who want to add more security at their doors
- Fast connection speed
- Camera can be viewed outside of an intercom call
- Improved low-light performance
- Motion detection
- Camera snapshots can be emailed to a customer's mobile device
- Dealer-configurable doorbell sounds

## Control4 DS2 Door Station

Model number	C4-DS2FM, C4-DS2FMKP, C4-DS2SM, C4-DS2SMKP
<b>Video</b>	
Camera resolution	1280 × 960 (W×H)
Camera view angle	120° × 90° × 145° (W×H×diagonal)
Camera IR night vision	Yes
Video stream codecs	H.263+, H.263, H.264, MJPEG, MPEG-4
<b>Audio</b>	
Microphone	Yes (integrated)
Speaker	2W
Acoustic pressure	78dB (1 kHz @ 1 meter distance)
Audio stream codecs	G.711, G.729
<b>Interface</b>	
Power	PoE 802.3af (Class 0 - 12.95W)
LAN	10/100Base-TX with Auto-MDIX, RJ-45
Relay outputs	NC/NO contacts, max 30V/1A AC/DC
Active output	8V-12VDC/400mA
<b>Dimensions</b>	
Surface mount	4.21 × 9.21 × 1.10 in. (107 × 234 × 28 mm) (W × H × D)
Flush mount	5.12 × 10.12 × 0.20 in. (130 × 257 × 5 mm) (W×H×thickness protruding from wall)
<b>Mechanical</b>	
Operating temperature	-40°F - 140°F (-40°C - 60°C)
Storage temperature	-40°F - 158°F (-40°C - 70°C)
Relative humidity	10% - 95% (non-condensing)
Protection level	IP 54
<b>Accessories</b>	
C4-DS2PLATE-BL	Adapter plate for old Door Station wall box Dimensions: 10.24 × 5.12 in. (260 × 130 mm)
C4-DS2BB	Wall box for DS2 Door Station Dimensions: <ul style="list-style-type: none"> <li>• Box: 4.41 × 9.53 × 1.85 in. (112 × 242 × 47 mm)</li> <li>• Wall cutout: 4.25 × 9.44 in. (108 × 240 mm)</li> </ul>

### For information on upgrading an old door station to the DS2 Door Station

Visit [ctrl4.co/ds2upgrade](http://ctrl4.co/ds2upgrade)